



EXTERIOR DIMENSIONS		
Wheelbase	104.7 in.	
Overall Length	182.3 in.	
Overall Width	73.6 in. (mirrors folded)	
	83.9 in. (mirrors unfolded)	
Overall Height (unloaded)	64.8	
Tread Width - Front	62.2 in. 61.8 in. (w/18" wheels)	
- Rear	62.2 in. 61.8 in. (w/18" wheels)	
Ground Clearance	6.9 in.	
Approach Angle	28.0 deg. 16.6 deg. (F SPORT)	
Departure Angle	22.9 deg.	

INTERIOR DI	MENSIONS	
Seating Capacity		5
Headroom	- Front	38.2 in. (w/o moonroof) 37.4 in. (w/ moonroof)
	- Rear	38.1 in. (w/o moonroof) 38.1 in. (w/ moonroof)
Legroom	- Front	42.8 in.
	- Rear	36.1 in.
Shoulder Room	- Front	57.3.in.
	- Rear	55.3 in.
Hip Room	- Front	55.1 in.
	- Rear	53.9 in.
Cargo Volume	- Rear seats up	17.7 cu. ft.
	- Rear seats folded down	54.6 cu. ft.

WEIGHTS AND CAPACITIES		
Curb Weight	3,940 lbs. (FWD)	
	4,050 lbs. (AWD)	
Gross Vehicle Weight	5,090 lbs. (FWD)	
	5,200 lbs. (AWD)	
Max Towing Capacity	2,000 lbs.	
Fuel Capacity	15.9 gal.	



## 2021 NX 300 Specifications

ENGINE	
Type, Materials	In-line 4-cylinder aluminum block and heads
Designation	8AR-FTS
Valvetrain	DOHC 16-valve with Dual VVT-iW
Displacement	2.0-liter twin-scroll turbocharged in-line 4- cylinder with intercooler
Bore x Stroke	3.40 in. x 3.40 in. (86.0 mm x 86.0 mm)
Compression Ratio	10.0:1
Horsepower	235 hp @ 4,800-5,600 rpm
Torque	258 lbft. @ 1,650-4,000 rpm
Fuel System	Electronic Fuel Injection (EFI, D-4ST)
Fuel Requirement	91-octane or higher unleaded
Emission Certification	LEV III ULEV 125

DRIVETRAIN			
Layout			e, full-time all-weather drive (AWD), ine, front-wheel drive (FWD)
Transmission Type			ulti-Mode Automatic Transmission, Ily Controlled Transmission with (ECT-i)
Designation		U661E	U661F
Gear Ratios		FWD	AWD
	<b>1</b> st	3.300	3.300
	$2^{nd}$	1.900	1.900
	$3^{rd}$	1.420	1.420
	4 <sup>th</sup>	1.000	1.000
	5 <sup>th</sup>	0.713	0.713
	6 <sup>th</sup>	0.608	0.608
	Reverse	4.148	4.148
Differential Ratio		3.888/4.11	7* (FWD)
*F.CDO.DT		3.888/4.11	7*/ 2.277 (AWD)

<sup>\*</sup>F SPORT



## 2021 NX 300 Specifications

CHASSIS AI	ND BODY	
Body/Frame		Unitized steel
Suspension	- Front	MacPherson strut, coil springs
	- Rear	Trailing arm double wishbone type, coil springs
Steering - Type	e	Electric Power Steering (EPS)
	- Turns (lock to lock)	2.68
	- Turning Radius (wall to wall) - Turning Radius (curb to curb)	19.9 ft. 18.7 ft.
Brakes	- Front - type/diameter	Ventilated Disc
	- Rear - type/diameter	Disc
Anti-lock Braki	ng System	4-channel, 4-sensor
Wheel Size/Typ	pe	17 x 7 in. (standard)
		$18 \times 7.5$ in. (stand-alone option, Premium/Luxury package and F SPORT)
Tire Size/Type		225/65R17 (standard)
		225/60R18 (stand-alone option, Premium/Luxury package and F SPORT all-season tire)
		235/55R18 (F SPORT summer tire)
Spare Tire/Wh	eel	T165/80D17 Compact spare

PERFORMANCE	
0-60 mph Acceleration (mfg. results)	7.0 sec. (AWD) 7.2 sec. (FWD)
Top Track Speed	124 mph – electronically limited
Lexus Estimated Fuel Economy* (City/Hwy/Combined)	22/28/24 (AWD) 22/28/25 (FWD) 22/27/24 (AWD F SPORT)
Coefficient of Drag (Cd)	0.34

<sup>\*</sup> Actual mileage will vary.